



| 呼径   | 外径    |                |                | 肉厚  |               |               | 面間    |                |                | 摘要 |
|------|-------|----------------|----------------|-----|---------------|---------------|-------|----------------|----------------|----|
|      | OD    |                |                | T   |               |               | A     |                |                |    |
|      |       | 素地             | 研磨             |     | 素地            | 研磨            |       | 素地             | 研磨             |    |
| 1S   | 25.4  | +0.25<br>-0.25 | +0.25<br>-0.35 | 1.2 | +0.3<br>-0.15 | +0.3<br>-0.3  | 55.0  | +0.5<br>-0.5   | +0.5<br>-0.5   |    |
| 1.5S | 38.1  | +0.25<br>-0.25 | +0.25<br>-0.35 | 1.2 | +0.3<br>-0.15 | +0.3<br>-0.3  | 70.0  | +0.5<br>-0.5   | +0.5<br>-0.5   |    |
| 2S   | 50.8  | +0.25<br>-0.25 | +0.25<br>-0.35 | 1.5 | +0.3<br>-0.25 | +0.3<br>-0.35 | 82.0  | +0.5<br>-0.5   | +0.5<br>-0.5   |    |
| 2.5S | 63.5  | +0.3<br>-0.3   | +0.3<br>-0.4   | 2   | +0.35<br>-0.3 | +0.35<br>-0.4 | 105.0 | +0.75<br>-0.75 | +0.75<br>-0.75 |    |
| 3S   | 76.3  | +0.3<br>-0.3   | +0.3<br>-0.4   | 2   | +0.4<br>-0.3  | +0.4<br>-0.4  | 110.0 | +0.75<br>-0.75 | +0.75<br>-0.75 |    |
| 4S   | 101.6 | +0.5<br>-0.5   | +0.5<br>-0.6   | 2   | +0.4<br>-0.4  | +0.4<br>-0.5  | 155.0 | +0.75<br>-0.75 | +0.75<br>-0.75 |    |
| 10A  |       |                |                |     |               |               |       |                |                |    |
| 15A  | 55.0  |                |                | 2.1 |               |               | 21.7  |                |                |    |
|      |       |                |                |     |               |               |       |                |                |    |
|      |       |                |                |     |               |               |       |                |                |    |

摘要

|    |                |    |    |    |
|----|----------------|----|----|----|
| 図番 | NGS-HL01       | 承認 | 審査 | 作成 |
| 品名 | サニタリーヘルールエルボ   |    |    |    |
| 材質 | SUS304、SUS316L |    |    |    |
| 作成 | 15.08.18       |    |    |    |